



Butt terminus

Control unit with printer

Shooter's monitor



Run control unit

Technical Specifications

| Caliber: | Up to 9.65mm / 0.38" |
|---|---|
| Hit Detection: | Electronic |
| Measuring Accuracy: | ≤ 5mm |
| Run Distance: | 10m |
| Run times for the target: | Slow runs 5 seconds Fast runs 2.5 seconds |
| Power: | Mains 3x 400/230V 50Hz |
| Dimensions: Butt terminus Program control unit Run control unit | 1300 x 1000 x 100 mm 270 x 430 x 470 mm 70 x 70 x 70 mm |
| Weight: Butt terminus Program control unit Run control unit | 30kg / 66lb 12kg / 26lb 0.1kg / 0.2lb |

Description

The tried and trusted ISSF Running Boar TG 171, with the addition of the most modern Electronic Hit Scoring System TG 5051 H, guarantees challenging shooting. The hit position is shown on the shooter's monitor within a fraction of a second, exactly and unerringly. The result can be printed out on demand.

Features

- Maximum operation security due to the most modern electronics
- Simple handling
- Graphic presentation of the hit position
- 3 zoom levels
- x / y coordinates and radius on monitor and printout
- Silent result printout (also graphically)
- Program Editor

Components

- Program control unit complete with microprocessor, thermo-printer and shooter's monitor
- Run control unit
- Butt terminus with target electronics mounted onto trolley
- Two-rail construction for 10m target track
- Data cables
- Power supply
- Barcode scanner to read-in shooting programs

Related Equipment

- PC for result printout and rank list
- Large screen and/or additional monitors
- LCD Monitor, Matrix Printer
- Remote Control